

Living Colors
Excellent Hiding Emulsion
122 series

PRODUCT INTRODUCTION

| | |
|------------------|---|
| Recommended Uses | Suitable for plastered interior concrete or cement walls. |
| Description | Living Colors series provides a collection of 1050 color choices with a color fandeck, and the product could be gotten speedily by a computer matching system in just a few minutes. Excellent Hiding Emulsion 122 series is a quality vinyl acrylic copolymer emulsion paint specially designed for interior decoration and protection of all masonry, concrete & plaster surfaces. |
| Features | <ul style="list-style-type: none"> ● Excellent hiding ● Anti-mould ● Low VOC ● Easy application ● No lead or mercury added |
| Standard Packing | 18L |

TECHNICAL DATA

| | |
|-------------------------------------|--|
| Base Resin | Vinyl Acetate , Acrylic Copolymer Emulsion |
| Color | Computer matched as per Living Colors fandeck with 1050 colors ; or tailor-made colors on request |
| Finish | Matt |
| Calculated Coverage | Around 12m ² /ltr. @25 microns dry film thickness per coat |
| Recommended Film Thickness Per Coat | <ul style="list-style-type: none"> ● Brush ---Wet : 105 microns ---Dry : 25 microns ● Roller ---Wet : 95 microns ---Dry : 25 microns |
| Drying Time | <ul style="list-style-type: none"> ● Touch Dry --- 1 hour ● Hard Dry --- 2 hours ● Overcoating --- minimum 3 hours, maximum indefinite. |

APPLICATION

| | |
|---------------------|--|
| Recommended Sealer | Camel Alkali Resistant Wall Sealer MA473 / Camel Water-Borne Sealer MA472 / Camel Solvent Based Sealer MA481 |
| Cleaning Solvent | Water |
| Recommended Thinner | Water |

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Living Colors
Excellent Hiding Emulsion
122 series

| APPLICATION | |
|--|---|
| Method of Application | <ul style="list-style-type: none"> ● Ready-to-use after thinning with clear water and stirring thoroughly ● Thinning Ratio By Brush --- Dilute 10 parts of paint with 3 parts of water by volume. By Roller --- Dilute 10 parts of paint with 2 parts of water by volume. By Airless spray --- Dilute 10 parts of paint with 1 parts of water by volume. By Conventional spray --- Dilute 10 parts of paint with 4 parts of water by volume. ● Recommended no. of coats --- 2 coats ● Recommended Application ---Painting is recommended to carry out on fine day. ---Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles. For recoating old surfaces, all chalked and scaled materials must be removed before painting. ---Stir the paint well before use. |
| SAFETY PRECAUTION | |
| Dangerous Goods Classification | Not applicable. |
| Shelf-Life | 36 Months. |
| Application Conditions | <ul style="list-style-type: none"> ● Maintain temperature in areas to receive coatings at minimum 4 deg. C, during application and until coatings have cured. ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post "Wet Coating" signs while work is in progress and while coatings are curing. |
| Product Storage & Handling | <ul style="list-style-type: none"> ● Net Weight ---Around 24 kg (18L pack) (values may vary with colors) ● Delivery & Handling ---Material to be delivered and stored in undamaged, original manufacturers' containers. ---Keep container closed when not in use. ---Stir the paint well before use. ---Store at cool, dry place. |
| Health & Safety Precautions | <ul style="list-style-type: none"> ● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. ● Eye contact --- Flush immediately with water and get medical care. ● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. ● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur. |
| Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong | Flat Coatings P09-02 |
| VOC content (ready to use) | Not exceeding 50gm/litre |

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.