

Living Colors
Acrylic Exterior Wall Finish (Full Gloss)
124 series

PRODUCT INTRODUCTION

Recommended Uses	Suitable for plastered exterior & interior concrete or cement walls.
Description	Living Colors series provides a collection of 1050 color choices with a color fandeck, and the product could be gotten speedily by a computer matching system in just a few minutes. Acrylic Exterior Wall Finish (Full Gloss) 124 series is a premium quality gloss emulsion paint specially designed for protection and decoration of exterior and interior wall surfaces. And there are 125 and 126 series to provide matt and semi gloss finishes respectively.
Features	<ul style="list-style-type: none"> ● Excellent weather resistance ● Excellent color retention ● Low VOC ● Anti-mould ● High hiding ● Washable & easy for maintenance ● Easy application ● No lead or mercury added ● High gloss finish
Standard Packing	5L & 16kg.

TECHNICAL DATA

Base Resin	Acrylic
Color	Computer matched as per Living Colors fandeck with 1050 colors ; or tailor-made colors on request
Standard Accelerated Weathering	No chalking, cracking & very slight color fading observed after 750 hours in UV / Condensation Screening Device.
Finish	Full gloss
Calculated Coverage	Around 13.3m ² /ltr. @30 microns dry film thickness per coat
Recommended Film Thickness Per Coat	<ul style="list-style-type: none"> ● Brush/Roller ---Wet : 100 microns ---Dry : 30 microns
Drying Time	<ul style="list-style-type: none"> ● Touch Dry --- 1 hour ● Hard Dry --- 2 hours ● Overcoating --- minimum 3 hours, maximum indefinite.
Product Standard	GB 9755-2001(Product have been submitted to National Research Center of Testing Techniques for Building Materials, result confirmed to be in Excellent Grade.

APPLICATION

Recommended Sealer	Camel Alkali Resistant Wall Sealer MA473 / Camel Water-Borne Sealer MA472 / Camel Solvent Based Sealer MA481
Recommended Undercoat	Camel Textured Base Coat MA471 (optional)
Cleaning Solvent	Water
Recommended Thinner	Water

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Living Colors Acrylic Exterior Wall Finish (Full Gloss) 124 series	
APPLICATION	
Method of Application	<ul style="list-style-type: none"> ● Ready-to-use after thinning with clear water and stirring thoroughly ● Thinning Ratio <p>By Brush --- Dilute 10 parts of paint with 2 parts of water by volume. By Roller --- Dilute 10 parts of paint with 1 parts of water by volume. By Airless spray --- Dilute 10 parts of paint with 1 parts of water by volume. By Conventional spray --- Dilute 10 parts of paint with 3 parts of water by volume.</p> <ul style="list-style-type: none"> ● Recommended no. of coats --- 2 coats ● Recommended Application <p>---Painting is recommended to carry out on fine day. ---Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles. For recoating old surfaces, all chalked and scaled materials must be removed before painting. ---Stir the paint well before use.</p>
SAFETY PRECAUTION	
Dangerous Goods Classification	Not applicable.
Shelf-Life	36 Months.
Application Conditions	<ul style="list-style-type: none"> ● Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post "Wet Coating" signs while work is in progress and while coatings are curing.
Product Storage & Handling	<ul style="list-style-type: none"> ● Net Weight <p>---Around 7kg (5L pack) and 16kg (16kg pack) (values may vary with colors)</p> <ul style="list-style-type: none"> ● Delivery & Handling <p>---Material to be delivered and stored in undamaged, original manufacturers' containers. ---Keep container closed when not in use. ---Stir the paint well before use. ---Store at cool, dry place.</p>
Health & Safety Precautions	<ul style="list-style-type: none"> ● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. ● Eye contact --- Flush immediately with water and get medical care. ● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. ● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Non-flat Coatings P09-06
VOC content (ready to use)	Not exceeding 150gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.