

CAMEL WASHABLE DISTEMPER AW1011
--

Product Introduction

RECOMMENDED USES	:	Design for use on new or previously painted interior masonry surface such as brickwork, plaster, cement & rendering.
DESCRIPTION	:	<p>AW1011 is a high quality water based paint which is application friendly & with high opacity which provide an economical value to end-user.</p> <ul style="list-style-type: none"> ● Washable ● Fungus & mould resistant ● High opacity ● Durable ● Quick drying ● No added lead & mercury
STANDARD PACKING	:	25 kg

Technical Data

BASE RESIN	:	Vinyl Acetate/Acrylic Copolymer Emulsion
COLOR	:	White
VOLUME SOLIDS	:	Approx. 31 %
FINISH	:	Matt
CALCULATED COVERAGE	:	Approx. 12.3 sq.m / ltr @ 25 microns dry film thickness.
RECOMMENDED FILM THICKNESS	:	Wet : 150-200 microns
(2 Coats in total)	:	Dry : 50-60 microns.
DRYING TIME	:	
Touch Dry	:	30 minutes
Over coating@20°C	:	
Minimum	:	2 - 3 hours
Maximum	:	- Indef.

Application

RECOMMENDED THINNER	:	Water
CLEANING SOLVENT	:	Water
METHOD OF APPLICATION	:	
By Brush	:	Dilute 10 parts of paint with 3 – 4 parts of water by volume.
By Roller	:	Dilute 10 parts of paint with 2 – 3 parts of water by volume.
By Airless Spray	:	Dilute 10 parts of paint with 2 – 3 parts of water by volume.
By Conventional Spray	:	Dilute 10 parts of paint with 3.5 – 4.5 parts of water by volume.

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.AW1011/0704/B/02

Page 1 of 2

CAMEL WASHABLE DISTEMPER AW1011
--

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	:	Not applicable.
SHELF-LIFE	:	36 Months.
APPLICATION CONDITIONS	:	<ul style="list-style-type: none"> All surfaces must be dry and free from grease, dirt, loose mortar, efflorescence and contaminants. Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. Adequately ventilate areas where coating is being applied. Maintain a reasonably dust-free atmosphere for duration of works. Protect adjacent surfaces not scheduled to receive coating from damage and overcoat. Post 'Wet Coating' signs while work is in progress and while coating are curing.
OTHER CONSIDERATIONS	:	<ul style="list-style-type: none"> Material to be delivered and stored in undamaged, original manufacturers' containers. Keep container closed when not in use. Stir the paint well before use. Store at cool, dry place.
HEALTH & SAFETY PRECAUTIONS	:	<ul style="list-style-type: none"> Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
REGULATED PRODUCT CODE	:	Flat Coatings P09-02
VOC CONTENT	:	≤ 50g/ltr

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.
 Content will be updated without prior notice.
 Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.AW1011/0704/B/02