

VIVA Wood Lacquer K220	
PRODUCT INTRODUCTION	
Recommended Uses	For interior decoration and re-decoration of wood surfaces.
Description	A fast drying wood lacquer with excellent rubbing and polishing properties. The high solid content prevents excessive penetration into porous wooden surfaces. The high film build provides good gloss retention and good resistance to water, alkali and alcohol.
Standard Packing	1L, 4L & 20L
TECHNICAL DATA	
Base Resin	Oleo resinous
Color	Clear
Finish	Gloss
Viscosity	Approx. 72KU (@25°C)
Calculated Coverage	Around 12m ² /ltr. @35 microns dry film thickness per coat
Drying Time	<ul style="list-style-type: none"> ● Touch Dry --- 20 minutes ● Hard Dry --- 24 hours ● Overcoating --- minimum 4 hours, maximum indefinite.
APPLICATION	
Method of Application	<ul style="list-style-type: none"> ● Thinning Ratio By Brush / Roller --- Ready for use, thinned with Camel White Turpentine 206 if necessary. ● Recommended no. of coats --- 2 coats (allowing 4 hours dry between coat) ● Recommended Application --- Painting is recommended to carry out on fine day. --- Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles. For recoating old surfaces, all chalked and scaled materials must be removed before painting. --- Stir the paint well before use.

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

VIVA
Wood Lacquer
K220

SAFETY PRECAUTION	
Dangerous Goods Classification	Cat.5, Class 2, Division 1
Shelf-Life	24 months
Application Conditions	<ul style="list-style-type: none"> ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post "Wet Coating" signs while work is in progress and while coatings are curing.
Product Storage & Handling	<ul style="list-style-type: none"> ● Delivery & Handling ---Material to be delivered and stored in undamaged, original manufacturers' containers. ---Keep container closed when not in use. ---Stir the paint well before use. ---Store at cool, dry place.
Health & Safety Precautions	<ul style="list-style-type: none"> ● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. ● Eye contact --- Flush immediately with water and get medical care. ● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. ● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Clear Wood Finishes (Lacquers) P10-01
VOC content (ready to use)	Not exceeding 550gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.